



Hyxi DCS

4G / WIFI+LAN

Easy Installation

Supports a maximum of 10 inverters
Plug-and-play

Safe and Reliable

Data transmission encryption to protect data security
Recovery data is supported to ensure no data loss

Intelligent O&M

Supports 4G, WIFI and Ethernet communication modes
Supports local and remote software upgrade, parameter configuration and alarm fault analysis

Hyxi
DCS

Product Model	HYX-DCS-4G	HYX-DCS-WL
General Data		
Max. Inverters Supported	10	10
Data Acquisition Interval	Default: 5 mins (1-15 mins Configurable)	
Connection Interface	USB	USB
Ethernet Interface	/	10M / 100M Ethernet
Installation	Plug-and-play	Plug-and-play
Indicator	LED+App	LED+App
Dimensions (W*H*D)	122*41*33mm	144*41*33mm
Weight	64g	68g
Degree of Protection	IP66	IP66
Power Consumption	2W	1W
Input Voltage	5V / 1A	5V / 1A
Wireless Parameter		
Wireless	4G:TDD-LTE, FDD-LTE 3G:SCDMA 2G:GSM/GPRS	WIFI:802.11b/g/n
Environment		
Operating Ambient Temperature	- 30 to +65°C	
Relative Humidity Range	0 ~ 100%RH, Non-condensing	
Storage Temperature Range	-40 to +70°C	

※ Design and specifications are subject to change without notice.

Ver 1.0-202401

Zhejiang Hyxi Technology Co., Ltd.

www.hyxi-power.com
support@hyxi-power.com