


Beta-300 Pro Automatic Abrasive Sectioning Machine

SECTIONING



2024

10 / 1

TROJAN (SUZHOU) MATERIAL TECHNOLOGY CO.,LTD

Beta-300 Pro Automatic Abrasive Sectioning Machine

Beta-300Pro is a fully automatic vertical metallographic cutting machine. It utilizes advanced intelligent control technology with full touchscreen operation. Equipped with a three axis industrial joystick and laser positioning, it features a larger cutting worktable for easier operation. The machine integrates various cutting methods and techniques, ensuring excellent cutting surfaces even for heavy-duty, large cross-section samples. Its intelligent cutting modes offer the highest level of repeatability.




Features:

- Featuring a 7-inch high-definition LCD touchscreen interface, capable of saving and customizing up to 20 sets of cutting parameters;
- X-Y-Z three-axis linkage enables fully automatic cutting, with laser alignment for precise positioning of the cutting location;
- Multiple cutting modes to meet the cutting requirements of various samples;
- Standard fast vise enables fast and secure sample clamping, with various optional fixtures available;
- Adjustable cutting force with intelligent optimization based on material hardness and preset parameters;
- Pulse cutting function with automatic speed adjustment for superi or cutting performance;
- Automatic judgment of cutting end function;
- Quick positioning function.



Unite: mm

Dimension Figure



www.trojanworld.com Discover the truth of material

Technical Data:

| Model | | Beta-300 Pro |
|---------------|------------------------|---|
| | Rotation speed | 800~3500rpm |
| Cutting blade | Diameter | Ф300mm |
| | Arbor size | 32mm |
| | Input | 3x380V/50Hz+ground line |
| Electronic | Rated power | Total power 5.0KW, Motor Power 4KW |
| | Emergency stop | Press to cut off the control circuit and main power |
| | Security door lock | When the door is open, it cannot be started; when it is running, the door is locked |
| Safety | Rocker | Requires two-hand control |
| | Overload protection | Automatic shutdown for overload current |
| | Cutting Force | Monitoring cutting force, automatic stop when exceeding the set value |
| | Display / Control | 7-inch touchscreen |
| Control | Z-axis feed | Automatic: 0.1~5mm/s |
| Control | Y-axis feed | Automatic : 0.1~5mm/s |
| | X-axis feed | Electric control rocker |
| | Capasity | 80L |
| | Dimension | 720x550x550mm (WxDxH, with paper pump) |
| Cooling | Connector | Inlet: DN15, High Pressure pipe of Φ19 inner diameter; outlet: 1.5 ", Flexible pipe of Φ38 inner diameter |
| | Water way | Two , flow: 50L/Min |
| | Cutting Mode | Vertical/ Horizontal/Vertical + Horizontal |
| | Speed control mode | Constant speed / Pulsing/ Automatic speed adjustment |
| Intelligent | Laser tool setting | Equipped |
| Cutting | Automatic tool setting | Equipped |
| | Automatic cut off | No need to set cutting depth, automatic stop after cut off |
| Cutting | Max. diameter | Ф110mm |
| Capacity | Max. Square section | 80x200mm |
| | Dimension | 280x536mm |
| Workbench | T-slot | 12mm |
| | Travel | X-axis: 80mm Y-axis: 200mm Z-axis: 150mm |
| Dimensions | W×D×H | 979×940×1535mm(Closed cover), 979×940×1881mm(open cover) |
| Weight | Beta 300 pro | 376kg |
| vvcigiit | Water tank | 34kg |

^{*}X: left-right; Y: front-back; Z: up-down.

www.trojanworld.com

Standard Accessories:

| 1 | Recirculating cooling and filter system | | Capacity: 80L, flow: 100L/Min | 1set |
|---|---|-------|--|-----------|
| 2 | Handlebar style fast-lock | 48 84 | S300L/R | 1set |
| 3 | 3 Open spanner 4 Allen key 5 Cutting blades fix | | 30 Open spanner | 1pc |
| 4 | | | 8mm Allen key | 1pc |
| 5 | | | Lock nut 1pcs+Fixing piece 2pcs | 1set |
| 6 | Inlet pipe | | Ф19mm Rubber pipe 1.5m | 1pc |
| 7 | Outlet pipe | 3 | Ф38mm steel wire pipe | 1pc |
| 8 | Abrasive Wheels | | A603020 (300*32*2.0) A503020 (300*32*2.0) | 5pcs each |

Optional Accessories:

| 1 | Large Vertical clamp | H400 |
|---|---------------------------------|------------|
| 2 | Fast vise | F300L/R |
| 3 | Padding block for vertical vise | H400-BLOCK |
| 4 | Extend arm | H400-EX |

www.trojanworld.com Discover the truth of material

Related Consumables & Accessories:







Coolant

Purchase list:

Abrasive Wheels:

| 01.01.160 | A60 Alumina Abrasive Wheels (Very hard ferrous metals) | A603020 | 300*32.0*2.0mm | 10pcs |
|-----------|--|---------|----------------|-------|
| 01.01.260 | A50 Alumina Abrasive Wheels (Medium hard ferrous metals) | A503020 | 300*32.0*2.0mm | 10pcs |
| 01.01.360 | A30 Alumina Abrasive Wheels (Soft ferrous metals) | A303020 | 300*32.0*2.0mm | 10pcs |
| 01.02.460 | S20 Abrasive Cut Off Wheels (Non-ferrous soft metals) | S203020 | 300*32.0*2.0mm | 10pcs |
| | | | | |

Diamond/CBN Cut Off Wheels:

| 01.03.570 | DP Electroplated Diamond Cut Off Wheels | DP303220 300*32.0*2.0mm | 1PC |
|-----------|---|----------------------------|-----|
| 01.04.670 | DR Resin-Bonded Diamond Cut Off Wheels | DR303220 300*32.0*2.0mm | 1PC |
| 01.05.770 | DM Metal-Bonded Diamond Cut Off Wheels | DM303220 300*32.0*2.0mm | 1PC |
| 01.10.970 | CBN-M BoronNitride Cut Off Wheels | CBN-M303220 300*32.0*2.0mm | 1PC |
| | | | |

Coolant:

| 01.07.810/820 | TJ 1220 Cutting Coolant | 1L/5L |
|---------------|-------------------------|-------|
| 01.07.857/860 | TJ 1410 Cutting Coolant | 1L/5L |
| 01.07.890/900 | TJ 1506 Cleaner | 1L/5L |



TROJAN (SUZHOU) MATERIAL TECHNOLOGY CO.,LTD

Tel: +86-512-65283666 Email: sales@trojanchina.com Web: www.trojanworld.com

Add: Building 26,No.228 Gongtang Road,Luzhi Town,Wuzhong Suzhou,China

